

Detailed Specifications

TOTAL MATERIAL WEIGHT 3111 grams per m²
Colour Gum Tree Green- Natural Green and Irish Green
Construction Twisted Mono Filament and KDK Polyethylene Fibrillated yarn
Environment Statement Non Carcinogenic No Lead Product
Elongation @ Break (%) 30-40%
Colour Fastness to Light Colourfastness Rating (Xenon Fading Lamp Test) 4-5 Standard. Ref 8 Blue Scales
UV Stability Huls Stabilisers represent State of the Art Technology. Our product offers the best stability to light exposure currently available.
PILE HEIGHT 55mm +/- 5%
Tuft Length mm 117mm
Machine Gauge mm 9.52mm
Stitch Rate Per Metre 17/10cm or 170/Metre
PRIMARY BACKING
Material Polypropylene Woven Heat Set UV Stabilised
Warp Denier Tex 465/515 UV
Weft Denier Tex 1100/1225 UVF
Construction No/10cm 94/59
Colour Black UV Stabilised Heat Shrunk
Weight (GMS/M²) 140
No. of Layers 2
SECONDARY BACKING
Compound Base Carboxylated Self Curing Styrene Buta-Diene Cross
Turf Anchorage Linked Rubber Latex 7.1 KGS per Tuft
Colour Black UV Stabilised Heat Shrunk
SUPPLIED AS
Roll Widths 3.72 Metre (others on request)
Roll Lengths 20m (others on request)
OPTIONS/REQUIREMENTS
Infill Fine Washed & Graded Silica Sand and Granulated Rubber
Perforation On Request
Limited Warranty 7 Years
PRODUCTS ARE TURFTED IN OUR AUSTRALIAN FACTORY WITH AUSTRALIAN MATERIALS AND CAN BE MADE TO MANY SPECIFICATIONS.