

## **Detailed Specifications**

TOTAL MATERIAL WEIGHT 5111 grams per m<sup>2</sup>  
Colour Gum Tree Green- Natural Green and Irish Green  
Construction Twisted Mono Filament and KDK Polyethylene Fibrillated yarn  
Environment Statement Non Carcinogenic No Lead Product  
Elongation @ Break (%) 30-40%  
Colour Fastness to Light Colourfastness Rating (Xenon Fading Lamp Test) 4-5 Standard. Ref 8 Blue Scales  
UV Stability Huls Stabilisers represent State of the Art Technology. Our product offers the best stability to light exposure currently available.

PILE HEIGHT 65mm +/- 5%  
Tuft Length mm 117mm  
Machine Gauge mm 9.52mm  
Stitch Rate Per Metre 21/10cm or 210/Metre

### **PRIMARY BACKING**

Material Polypropylene Woven Heat Set UV Stabilised  
Warp Denier Tex 465/515 UV  
Weft Denier Tex 1100/1225 UVF  
Construction No/10cm 94/59  
Colour Black UV Stabilised Heat Shrink  
Weight (GMS/M<sup>2</sup>) 140  
No. of Layers 2

### **SECONDARY BACKING**

Compound Base Carboxylated Self Curing Styrene Buta-Diene Cross  
Turf Anchorage Linked Rubber Latex 7.1 KGS per Tuft  
Colour Black UV Stabilised Heat Shrink

### **SUPPLIED AS**

Roll Widths 3.72 Metre (others on request)  
Roll Lengths 20m (others on request)

### **OPTIONS/REQUIREMENTS**

**Infill Fine Washed & Graded Silica Sand and Granulated Rubber**  
**Perforation On Request**  
**Limited Warranty 7 Years**